KOYO MARU

Ocean-going Salvage Tug



| IMO No. | 9966348 |
|---|--|
| Call Sign | 7KPX |
| Classification | NK (NS*, TV, DPS 2, NC, IHM, Nox-III (SCR), MNS*, M0) |
| When Built | June 2024 |
| Flag | Japan |
| Port of Registry | Tokyo |
| Gross Tonnage | 2,906 |
| Length (O.A.) \times Breadth \times Depth | 80.64m × 15.50m × 6.75m |
| Speed | Cruising 12kt |
| | Maximum 14.5kt |
| Range | 14,500nm at 12kt |
| | 7,500nm at 14.5kt |
| Main Engines / NOx SCR | Diesel, DAIHATSU 8DKM-36e × 2 / 196VB |
| | MCR 4,500kW × 600/154rpm x 2 = 9,000kW (approx. 12,069hp) |
| Bollard Pull | 161.2mt |
| Propellers | CPP in fixed Kort Nozzle × 2 |
| Rudders | Schilling rudder × 2 |
| Bow Thrusters | Electric propulsion CPP, 575kW × 2, 10t thrust each |
| Stern Thruster | Electric propulsion CPP, 670kW × 1, 10t thrust |
| Navigational Devices | Doppler Current Meter, AIS, DGPS, Kongsberg Maritime K-Pos DP21, ECDIS x 2 |
| Communication Devices | VHF, GMDSS, VSAT, Iridium Certus |
| Generators / NOx SCR | AC450V × 1,250kVA × 3 / 49VB |
| Towing Winch | 2 drums, 45t × 20m/min (Brake capacity 300t) |
| Tow Wire | 71mm × 1,200m (Main) |
| | 70mm x 1,200m (Spare) |
| Deck Crane | 15t × 15m |
| External Fire-Fighting | Fire-fighting pump driven by port main engine $1,920 \text{m}^3/\text{h} \times 140 \text{m} \times 1$ |
| | Twin Monitors: Electric control fire-fighting water gun 20,000L/min $	imes$ 10bar $	imes$ 1 |
| | Electric control fire-fighting water (or foam) gun 12,000L/min $	imes$ 10bar $	imes$ 1 |
| | Water curtain nozzle for cooling hull 125L/min × 0.5MPa × 20 |
| Deck Space | Aft. Upper Deck 310m ² |
| | Boat Deck approx. 150m ² |
| Salvage Store | 448m ³ |
| Accommodation | 43 persons excluding ship's crew |
| | |